APPARATUS AND METHOD FOR CLEANING MEMBRANE FILTRATION MODULES


Also published as: Publication number: JP2002525197 (T) WO0018498 (A1) Publication date: 2002-08-13 JS2001047962 (A1) Inventor(s): US6524481 (82) Applicant(s): TW222895 (B) Classification: NZ510394 (A) B01D63/02; B01D 65/02; B01D65/08; B01D69/08; C02F3/12; C12M1/40; B01D63/02; B01D 65/00; B01D69/00; C02F3/12; C12M1/40; (IPC1-7): B01D63/02; B01D65/02; - international: CN1319032 (A) CN1147349 (C) CA2342346 (A1) B01D69/08; C12M1/40 CA2342346 (C) B01D63/02; B01D63/02D; B01D65/02; B01D65/08B10; - European:

C02F3/12P2 Application number: JP20000572010T 19990924

Priority number(s): AU1998PP 06217 19980925; AU1998PP06218 19980 925; AU1999PQ01112 199906 21; WO1999AU00817 19990924

Abstract not available for JP 2002525197 (T) Abstract of corresponding document: WO 0018498 (A1)

A method and apparatus for cleaning a membrane module (5), the membrane module comprising a plurality of porous membranes (6), said membranes being arranged in close proximity to one another and mounted to prevent excessive movement therebetween, and means (10, 12) for providing, from within the module (5), by means other than gas passing through the pores of said membranes, gas bubbles entrained in a liquid flow such that, in use, said liquid and bubbles (18) entrained therein move past the surfaces of said membranes to dislodge fouling materials therefrom, said gas bubbles being entrained in said liquid by flowing said liquid past a source of gas to draw the gas into said liquid flow. The gas bubbles are entrained into the liquid using a venturi type device (12). The membranes (20) are preferably partitioned into discrete groups (23) to assist cleaning white maintaining high packing density.



<< less

Data supplied from the espacenet database — Worldwide